

一、韩国AUTONICS自控元器件

(十) 接近开关

外型	型号	检测距离	电源	规格	市场价			
	PRT08-1.5DO,1.5DC	1.5mm	24V DC (20-30V DC)	电感圆柱型 直流2线 DO:常开输出 DC:输出常闭	140			
	PRT08-2DO,2DC	2mm			140			
	PRT12-2DO,2DC	2mm			121			
	PRT12-4DO,4DC	4mm			121			
	PRT18-5DO,5DC	5mm			121			
	PRT18-8DO,8DC	8mm			121			
	PRT30-10DO,10DC	10mm			130			
	PRT30-15DO,15DC	15mm			130			
	PR08-1.5DN,1.5DP	1.5mm	12-24VDC (10-30VDC)	电感圆柱型 直流3线 DN:NPN输出 DP:PNP输出	140			
	PR08-1.5DN2,1.5DP2				140			
	PR08-2DN,2DP2	2mm			140			
	PRS12-2DN,2DP	2mm	12-24VDC (10-30VDC)	直流短型3线 DN:NPN常开输出 DP:PNP常开输出	130			
	PRS12-2DN2				130			
	PRS12-4DN,4DP	4mm			130			
	PRS12-4DN2				130			
	PR12-2DN,2DP	2mm	12-24VDC (10-30VDC)	电感圆柱型 直流3线 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	121			
	PR12-2DN2,2DP2				121			
	PR12-4DN,4DP	4mm			121			
	PR12-4DN2,4DP2				121			
	PR18-5DN,5DP	5mm	12-24VDC (10-30VDC)		121			
PR18-5DN2,5DP2	121							
PR18-8DN,8DP	8mm			121				
PR18-8DN2,8DP2				121				
	PR30-10DN,10DP	10mm	12-24VDC (10-30VDC)	电感圆柱型直流3线 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	141			
	PR30-10DN2,10DP2				141			
	PR30-15DN,15DP	15mm			141			
	PR30-15DN2,15DP2				141			
	PR12-2AO,2AC	2mm	110V- 220VAC (90- 250VAC)	电感圆柱型 交流2线 AO:常开输出 AC:输出常闭	143			
	PR12-4AO,4AC	4mm			143			
	PR18-5AO,5AC	5mm			143			
	PR18-8AO,8AC	8mm			143			
	PR30-10AO,10AC	10mm			156			
	PR30-15AO,15AC	15mm			156			
	PRL08-1.5DN,1.5DP	1.5mm	12-24VDC (10-30VDC)	直流2线长型 DN:NPN常开输出 DP:PNP常开输出	181			
	PRL08-1.5DN2,1.5DP2							
	PRL08-2DN,2DP	2mm				130		
	PRL08-2DN2,2DP2							
	PRL12-2DN,2DP	2mm	VDC (10-30)			130		
	PRL12-4DN,4DP	4mm				130		
	PRL18-5DN,5DP	5mm						130
	PRL18-5DN2,5DP2							130
	PRL18-8DN,8DP	8mm						130
	PRL18-8DN2,8DP2							130
PRL30-10DN,10DP	10mm						156	
PRL30-10DN2,10DP2							156	
PRL30-15DN,15DP	15mm	12-24VDC		156				
PRL30-15DN2,15DP2				156				
PRL18-5AO,5AC	5mm	AC100- 240V	交流2线长型 AO:常开输出 AC:输出常闭	143				
PRL18-8AO,8AC	8mm			143				
PRL30-10AO,10AC	10mm			170				

PRL30-15AO,15AC	15mm		AC:棚出吊钩	170
PRCMT12-2DO,2DC	2mm	DC24V	电感圆柱型 直流2线 接插型 DO:常开输出 DC:输出常闭	130
PRCMT12-4DO,4DC	4mm			130
PRCMT18-5DO,5DC	5mm			130
PRCMT18-8DO,8DC	8mm			130
PRCMT30-10DO,10DC	10mm			143
PRCMT30-15DO,15DC	15mm			143
PRCM12-2DN,2DP	2mm			12-24VDC
PRCM12-2DN2,2DP2		130		
PRCM12-4DN,4DP	4mm	130		
PRCM12-4DN2,4DP2		130		
PRCM18-5DN,5DP	5mm	12-24VDC	电感圆柱型 直流标准 接插型 DO:常开输出 DC:输出常闭	130
PRCM18-5DN2,5DP2				130
PRCM18-8DN,8DP	8mm			130
PRCM18-8DN2,8DP2				130
PRCM30-10DN,10DP	10mm	12-24VDC		156
PRCM30-10DN2,10DP2				156
PRCM30-15DN,15DP	15mm			156
PRCM30-15DN2,15DP2				156
PRCM12-2AO,2AC	2mm	110V- 220VAC (90- 250VAC)	电感圆柱型 交流标准 接插型 AO:常开输出 AC:输出常闭	164
PRCM12-4AO,4AC	4mm			
PRCM18-5AO,5AC	5mm			
PRCM18-8AO,8AC	8mm			
PRCM30-10AO,10AC	10mm			
PRCM30-15AO,15AC	15mm			192
PRCML18-5DN,5DP	5mm	12-24VDC (10-30VDC)	电感圆柱型 直流加长 接插型 DN:NPN常开输出DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP 常闭输出	143
PRCML18-5DN2,5DP2				143
PRCML18-8DN,8DP	8mm			143
PRCML18-8DN2,8DP2				143
PRCML30-10DN,10DP	10mm	12-24VDC (10-30VDC)		183
PRCML30-10DN2,10DP2				183
PRCML30-15DN,15DP	15mm			183
PRCML30-15DN2,15DP2				183
PRCML18-5AO,5AC	5mm	110V- 220VAC (90- 250VAC)		164
PRCML18-8AO,8AC	8mm			
PRCML30-10AO,10AC	10mm			
PRCML30-15AO,15AC	15mm			192
PRWT12-2DO,2DC	2mm	12-24VDC	电感圆柱型 直流2线电缆接插型 DO:常开输出 DC:输出常闭	137
PRWT12-4DO,4DC	4mm			
PRWT18-5DO,5DC	5mm			
PRWT18-8DO,8DC	8mm			
PRWT30-10DO,10DC	10mm			
PRWT30-15DO,15DC	15mm	DC24V	100HZ, 外露型	164
PRW12-2DN,2DP	2mm	12-24VDC (10-30VDC)		137
PRW12-2DN2,2DP2				
PRW12-4DN,4DP	4mm			
PRW12-4DN2,4DP2				
PRW18-5DN,5DP	5mm	12-24VDC (10-30VDC)		137
PRW18-5DN2,5DP2				
PRW18-8DN,8DP	8mm			
PRW18-8DN2,8DP2				
PRW30-10DN,10DP	10mm	12-24VDC	电感圆柱型 电缆输出接插型 DN:NPN常开输出DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP	164
PRW30-10DN2,10DP2				

PRW30-15DN,15DP	15mm	(10-30VDC)	常闭输出	164		
PRW30-15DN2,15DP2						
PRW12-2AO,2AC	2mm	110V- 220VAC (90- 250VAC)		164		
PRW12-4AO,4AC	4mm					
PRW18-5AO,5AC	5mm					
PRW18-8AO,8AC	8mm					
PRW30-10AO,10AC	10mm					
PRW30-15AO,15AC	15mm					
PRWL18-5DN,5DP	5mm	12-24VDC (10-30VDC)	电感圆柱型 加长电缆输出接插型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP 常闭输出	144		
PRWL18-5DN2,5DP2						
PRWL18-8DN,8DP	8mm	12-24VDC (10-30VDC)		171		
PRWL18-8DN2,8DP2						
PRWL30-10DN,10DP	10mm	12-24VDC (10-30VDC)		171		
PRWL30-10DN2,10DP2						
PRWL30-15DN,15DP	15mm	110V- 220VAC (90- 250VAC)		164		
PRWL30-15DN2,15DP2						
PRWL18-5AO,5AC	5mm	110V- 220VAC (90- 250VAC)		192		
PRWL18-8AO,8AC	8mm					
PRWL30-10AO,10AC	10mm					
PRWL30-15AO,15AC	15mm					
PRAT12-2DO,2DC	2mm	24V DC (20-30V DC)	直流2线防溅型DO:常开输出DC:输出 常闭	222		
PRAT18-5DO,5DC	5mm			244		
PRAT30-10DO,10DC	10mm			301		
PRA12-2DN,2DP	2mm	12-24VDC (10-30VDC)	电感圆柱型 防溅型 DN:NPN常开输出 DP:PNP常开输 出 DN2:NPN常闭输出 DP2:PNP常闭输出	222		
PRA12-2DN2,2DP2				222		
PRA18-5DN,5DP	5mm			244		
PRA18-5DN2,5DP2				244		
PRA30-10DN,10DP	10mm			301		
PRA30-10DN2,10DP2				301		
PRA12-2AO,2AC	2mm	110V- 220VAC (90- 250VAC)		241		
PRA18-5AO,5AC	5mm			261		
PRA30-10AO,10AC	10mm			313		
CR18-8DN,8DP	8mm	12-24VDC (10-30VDC)	DN:NPN常开输出DP:PNP常开输出 DN2:NPN常闭输出	183		
CR18-8DN2				183		
CR30-15DN,15DP	15mm	220VAC电容 圆柱型	AO:常开输出 AC:输出常闭	222		
CR30-15DN2				222		
CR18-8AO,8AC	8mm			222		
CR30-15AO,15AC	15mm			261		
PSNT17-5DO,5DC	5mm	DC24V	700HZ,常开/常闭	70		
PSNT17-5DOU,5DCU				700HZ,常开/常闭,上面探测型		
PS12-4DN,4DP,4DN2	4mm	12-24VDC (10-30VDC)	电感方型	DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DNU:NPN常开输出,上面 检测型DPU:PNP常开输 出,上面检测型DN2U:NPN 常闭输出,上面检测型	500HZ	
PS12-4DNU,4DPU,4DN2U					117	
PSN17-5DN,5DP,5DN2	5mm				700HZ	
PSN17-5DNU,5DPU					70	
PSN17-5DN2U	8mm				200HZ	
PSN17-8DN,8DP,8DN2					70	
PSN17-8DNU,8DPU					200HZ,双频 率型	70
PSN17-8DN2U						
PSN17-8DN,8DP,8DN2-F					70	
PSN17-8DNU,8DPU-F						
PSN17-8DN2U-F						
PS50-30DN,30DP	30mm				500HZ	
					235	

PS50-30DN2,30DP2	50mm		50HZ	255			
AS80-50DN3,50DP3	50mm	DC12-48V	100HZ	554			
PFI25-8DN,8DP	8mm	DC12-24VDC 直流扁平型	200HZ				
PFI25-8DN2,8DP2							
PSN25-5DN,5DP	5mm	12-24VDC (10-30VDC)	直流新式方型DN:NPN常 开输出DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	300HZ	98		
PSN25-5DN2,5DP2				98			
PSN30-10DN,10DP	10mm			250HZ	117		
PSN30-10DN2,10DP2	10mm						
PSN30-15DN,15DP	15mm			200HZ	156		
PSN30-15DN2,15DP2	15mm						
PSN40-20DN,20DP	20mm			100HZ	156		
PSN40-20DN2,20DP2	20mm						
PSN25-5AO,5AC	5mm			AC100-240V	交流新式方型 A0:常 开输出 AC:输出常闭	20HZ	130
PSN30-10AO,10AC	10mm						143
PSN30-15AO,15AC	15mm	222					
PSN40-20AO,20AC	20mm	117					
PET18-5	5mm						
PT4-2D,3DN,3DP	4路中继连接盒	DC12-24V	2D:DC2线使用		444		
PT6-2D,3DN,3DP	6路中继连接盒		3DN:DC3线NPN使用		509		
PT8-2D,3DN,3DP	8路中继连接盒		3DP:DC3线PNP使用		574		
P96-M12-1	防水盖	防水盖可保护平时很少用的连接器孔渗水或渗油		21			
P90-M12,M18,M30	接近传感器固 定架	齐平型圆柱接近开关适用		4			
P90-R12,R18,R30		圆柱型接近开关适用		4			
连接器防 护罩	PT1-D,A	面板安装连接头(适用于DC/AC外露型接近开关)		39			
	PT2-D,A	面板安装连接头(适用于DC/AC平头型接近开关)		39			

(十一) 连接线缆

型号	线长	材料	类型	市场价
CID2-2, 3-2,2-2-I	2M直头	PVC: 乙烯基 (标准)	插座型	46
CLD2-2,3-2,2-2-I	2M弯头			46
CIA2-2,CLA2-2	2M			46
CID2-5,3-5,2-5-I	5M直头	PVC: 乙烯基 (标准)	插座型	65
CLD2-5,3-5,2-5-I	5M弯头			65
CIA2-5,CLA2-5	5M			65
C1D4-2,C2D4-2	2M	PVC: 乙烯基 (标准)	DC型(插头-插座)	65
C1D4-2P				
C3D4-2,C4D4-2				
C1A4-2,C2A4-2	2M		AC型(插座-插头)	65
C1A4-2P				
C3A4-2,C4A4-2				
C1D4-5,C2D4-5	5M	PVC: 乙烯基 (标准)	DC型(插头-插座)	83
C1D4-5P				
C2D4-2,C3D4-2				
C3D4-5,C4D4-5	5M		83	
C1A4-5,C2A4-5	5M		AC型(插座-插头)	83
C1A4-5P				
C3A4-5,C4A4-5				
CID2-2P,CLD2-2P	2M	PVC: 乙烯基 (标准)	插头型	46
CID2-5P,CLD2-5P	5M			65
CID3-2P,CLD3-2P	2M			46
CID3-5P,CLD3-5P	5M			65
CIA2-2P,CLA2-2P	2M			46
CIA2-5P,CLA2-5P	5M			65

	GID4-2P			65
	GID4-5P			85
	GIA4-2P			65
	GIA4-5P			85

(十二) 传感器控制器

外型	型号	功能	输出	说明	电源	市场价
	PA-12	通用型	定时1c	NPN/PNP内部转换 输入	AC110/220V	143
	PA10-U	高功能	定时1c	NPN输入	AC100-240V	372
	PA10-V,VP	通用	NPN	NPN/PNP输入		323
	PA10-W,WP	2通道	定时2c	NPN/PNP输入		

(十三) 开关电源

外型	型号	说明	电源	市场价
	SP-0305	输出3W-5VDC-0.6A 输入:220VAC	AC100-240V	183
	SP-0312	输出3W-12VDC-0.25A 输入:220VAC		
	SP-0324	输出3W-24VDC-0.13A 输入:220VAC	AC100-240V	183
	SPA-030-05	输出30W-5VDC-6A 输入:220VAC		
	SPA-050-05	输出50W-5VDC-10 A 输入:220VAC		
	SPA-030-12	输出30W-12VDC-2.5A 输入:220VAC		
	SPA-050-12	输出50W-12VDC-4.2A 输入:220VAC		
	SPA-030-24	输出30W-24VDC-1.25A 输入:220VAC		
	SPA-050-24	输出50W-24VDC-2.1A 输入:220VAC		
	SPA-075-24	输出75W-24VDC	AC100-120/AC200-240V	750
	SPA-100-24	输出100W-24VDC		742

(十四) 压力传感器

外型	型号	检测距离	压力种类	压力范围	电源	市场价	
配件	PSA-V01(P)	正方形	负压型	0.0~-101.3kPa	DC12-24V	652	
	PSA-01(P)		标准型	0.0~100.0kPa			
	PSA-1(P)		标准型	0.01~1000kPa			
	PSA-C01(P)		复合型	-100.0~100.0kPa			
	PSB-V01(P)	长方形	负压型	0.0~-101.3kPa	DC12-24V	652	
	PSB-01(P)		标准型	0.0~100.0kPa			
	PSB-1(P)		标准型	0.01~1000kPa			
	PSB-C01(P)		复合型	-100.0~100.0kPa			
		PSO-01	PSA外壳(黑色)				44
		PSO-02	PSO-01 保护盖				30

(十五) 步进电机/驱动器/控制器

步进电机 驱动器	型号	外型尺寸	驱动电流	驱动方式		电源	市场价
	KR5MC	77×45×32	1.4A	0.72/0.36		0-40VDC 3	1189
	KR-55MC	105×74×38		Micro STEP(0.009)			2000
	MD5-MF14	170×130×39				100-240VAC	
	KR-505G	215×150×62	2.8A	0.72/0.36		100-115VAC	3130
标准单轴型 (5线型)	型号	外型尺寸	激磁最大静 止转矩	重量(kg)	额定电流 (A/相)	转子惯性 惯量	市场价
	A1K-S543	□42×L33mm	1.3	0.25	0.75	35	617
	A2K-S544	□42×L39mm	1.8	0.3		54	657
	A3K-S545	□42×L47mm	2.4	0.4		68	
	A4K-S564	□60×L48.5mm	4.2	0.6	0.75	175	710
	A4K-M564				1.4		575
	A8K-S566	□60×L59.5mm	8.3	0.8	0.75	280	743
	A8K-M566				1.4		603
	A16K-M569	□60×L89mm	16.6	1.3	1.4	560	794
	A16K-G569				2.8		1164
	A21K-M596	□85×L68mm	21	1.7	1.4	1400	1612

	A21K-G596	□85×L68mm	21	1.7	2.8	1400	1712
	A41K-M599	□85×L98mm	41	2.8	1.4	2700	2283
	A41K-G599				2.8		
	A63K-M5913	□85×L128mm	63	2.8	1.4	4000	2841
	A63K-G5913				2.8		2991
标准单轴型 (标准结 线: 10线)	A1K-S543-S	□42×L33mm	1.3	0.25	0.75	35	712
	A2K-S544-S	□42×L39mm	1.8	0.3		54	754
	A3K-S545-S	□42×L47mm	2.4	0.4		68	
	A4K-S564-S	□60×L48.5mm	4.2	0.6	0.75	175	821
	A4K-M564-S				1.4		672
	A8K-S566-S	□60×L59.5mm	8.3	0.8	0.75	280	856
	A8K-M566-S				1.4		699
	A16K-M569-S	□60×L89mm	16.6	1.3	1.4	560	891
	A16K-G569-S				2.8		1094
	A21K-M596-S	□85×L68mm	21	1.7	1.4	1400	1712
	A21K-G596-S				2.8		
	A41K-M599-S	□85×L98mm	41	2.8	1.4	2700	2390
	A41K-G599-S				2.8		
	A63K-M5913-S	□85×L128mm	63	3.8	1.4	4000	2949
	A63K-G5913-S				2.8		
标准双轴型 (5线型)	A1K-S543W	□42×L33mm	1.3	0.25	0.75	35	645
	A2K-S544W	□42×L39mm	1.8	0.3		54	685
	A3K-S545W	□42×L47mm	2.4	0.4		68	
	A4K-S564W	□60×L48.5mm	4.2	0.6	0.75	175	727
	A4K-M564W				1.4		590
	A8K-S566W	□60×L59.5mm	8.3	0.8	0.75	280	759
	A8K-M566W				1.4		617
	A16K-M569W	□60×L89mm	16.6	1.3	1.4	560	809
	A16K-G569W				2.8		1178
	A21K-M596W	□85×L68mm	21	1.7	1.4	1400	1639
	A21K-G596W				2.8		
	A41K-M599W	□85×L98mm	41	2.8	1.4	2700	2347
	A41K-G599W				2.8		
	A63K-M5913W	□85×L128mm	63	3.8	1.4	4000	2878
	A63K-G5913W				2.8		3066
标准双轴型 (10线型)	A1K-S543W-S	□42×L33mm	1.3	0.25	0.75	35	727
	A2K-S544W-S	□42×L39mm	1.8	0.3		54	767
	A3K-S545W-S	□42×L47mm	2.4	0.4		68	
	A4K-S654W-S	□60×L48.5mm	4.2	0.6	0.75	175	839
	A4K-M654W-S				1.4		685
	A8K-S566W-S	□60×L59.5mm	8.3	0.8	0.75	280	873
	A8K-M566W-S				1.4		712
	A16K-M569W-S	□60×L89mm	16.6	1.3	1.4	560	904
	A16K-G569W-S				2.8		1110
	A21K-M596W-S	□85×L68mm	21	1.7	1.4	1400	1755
	A21K-G596W-S				2.8		
	A41K-M599W-S	□85×L98mm	41	2.8	1.4	2700	2445
	A41K-G599W-S				2.8		
	A63K-M5913W-S	□85×L128mm	63	3.8	1.4	4000	3003
	A63K-G5913W-S				2.8		
标准单孔型	AH1K-S543	□42×L33mm	1.3	0.25	0.75	35	1162
	AH2K-S544	□42×L39mm	1.8	0.3		54	1120
	AH3K-S545	□42×L47mm	2.4	0.4		68	1088
	AH4K-S564	□60×L48.5mm	4.2	0.6		175	1202

	AH4K-M564	□60×L48.5mm	4.2	0.6	1.4	175	1202
	AH8K-S566	□60×L59.5mm	8.3	0.8	0.75	280	1235
	AH8K-M566				1.4		
	AH16K-M569	□60×L89mm	16.6	1.3	1.4	560	1438
	AH16K-G569				2.8		
	AH21K-M596	□85×L68mm	21	1.7	1.4	1400	1950
	AH21K-G596				2.8		1952
标准双孔型	AH41K-M599	□85×L98mm	41	2.8	1.4	2700	3219
	AH41K-G599				2.8		
	AH63K-M5913	□85×L128mm	63	3.8	1.4	4000	2604
	AH63K-G5913				2.8		2608
	AH4K-S564W	□60×L48.5mm	4.2	0.6	0.75	175	1217
	AH4K-M564W				1.4		
	AH8K-S566W	□60×L59.5mm	8.3	0.8	0.75	280	1250
	AH8K-M566W				1.4		
	AH16K-M569W	□60×L89mm	16.6	1.3	1.4	560	1454
	AH16K-G569W				2.8		
	AH21K-M596W	□85×L68mm	21	1.7	1.4	1400	1968
	AH21K-G596W				2.8		1970
	AH41K-M599W	□85×L98mm	41	2.8	1.4	2700	3240
	AH41K-G599W				2.8		
	AH63K-M5913W	□85×L128mm	63	3.8	1.4	4000	2622
	AH63K-G5913W				2.8		2624
减速机型 (单轴, 5 线结线)	A35K-M566-G5	□60×L94.5mm	35	1:5	1.4	280	2252
	A40K-M566-G7.2		40	1:7.2			
	A50K-M566-G10		50	1:10			
	A140K-M599-G5	□85×L146mm	140	1:5	1.4	2700	3038
	A140K-G599-G5				2.8		3114
	A200K-M599-G7.2				1.4		3198
	A200K-G599-G7.2		200	1:7.2	2.8		3228
	A200K-M599-G10		200	1:10	1.4		3226
	A200K-G599-G10				2.8		3200
	减速机型 (双轴, 5		A35K-M566W-G5	□60×L94.5mm	35		1:5
A40K-M566W-G7.2		40	1:7.2				
A50K-M566W-G10		50	1:10				
	A140K-M599W-G5	□85×L146mm	140	1:5	1.4	2700	3082
	A140K-G599W-G5				2.8		3128
	A200K-M599W-G7.2				1.4		3202
	A200K-G599W-G7.2		200	1:7.2	2.8		3202
	A200K-M599W-G10		200	1:10	1.4		3204
	A200K-G599W-G10				2.8		3212
	减速机型+ 带电磁制动		A35K-M566-GB5	□60×L136mm	35		1:5
A40K-M566-GB7.2		40	1:7.2		2810		
A50K-M566-GB10		50	1:10		2824		
	A140K-M599-GB5	□85×L	140	1:5	1.4	2700	4268
	A140K-G599-GB5				2.8		4342
	A200K-M599-GB7.2				1.4		4420
	A200K-G599-GB7.2		200	1:7.2	2.8		4458
	A200K-M599-GB10		200	1:10	1.4		4420
	A200K-G599-GB10				2.8		4458
	带电磁震动		A4K-S564-B	□60×L90mm	4.2		0.9
A4K-M564-B		1.4					
A8K-S566-B		□60×L101mm	8.3	1.1	0.75	280	1577
A8K-M566-B					1.4		
A16K-M569-B		□60×L130.5mm	16.6	1.6	1.4	560	1854
A16K-G569-B					2.8		

步进马达	型号	外型尺寸	激磁最大静止转矩	减速比	额定电流 (A/相)	转子惯性 惯量	市场价
	A35K-M566-R5	□60×L59.5mm	35	1:5	1.4	280	2030
	A35K-M566W-R5			2050			
	A40K-M566-R7.2		40	1:7.2			1992
	A40K-M566W-R7.2			1984			
	A50K-M566-R10		50	1:10			2054
	A50K-M566W-R10						2074
	A35K-M566-RB5	□60×L101mm	35	1:5	1.4	280	2906
	A40K-M566-RB7.2			40			1:7.2
	A50K-M566-RB10		50				1:10