

6、3UA系列热过载继电器

型 号	整定电流范围(A)	单价	型 号	整定电流范围(A)	单价
3UA5040-0A	0.1-0.16	124.3	3UA5540-8M	36-45	155.1
3UA5040-0C	0.16-0.25	124.3	3UA5840-2B	12.5-20	206
3UA5040-0E	0.25-0.4	124.3	3UA5840-2C	16-25	206
3UA5040-0G	0.4-0.63	124.3	3UA5840-2D	20-32	206
3UA5040-0J	0.63-1	124.3	3UA5840-2E	25-40	206
3UA5040-0K	0.8-1.25	124.3	3UA5840-2F	32-50	206
3UA5040-1A	1-1.6	124.3	3UA5840-2T	40-57	206
3UA5040-1B	1.25-2	124.3	3UA5840-2P	50-63	258
3UA5040-1C	1.6-2.5	124.3	3UA5840-2V	57-70	258
3UA5040-1D	2-3.2	124.3	3UA5840-2U	63-80	258
3UA5040-1E	2.5-4	124.3	3UA5840-8W	70-88	258
3UA5040-1F	3.2-5	124.3	3UA5940-0A	0.1-0.16	145.9
3UA5040-1G	4-6.3	124.3	3UA5940-0C	0.16-0.25	145.9
3UA5040-1H	5-8A	124.3	3UA5940-0E	0.25-0.4	145.9
3UA5040-1J	6.3-10	124.3	3UA5940-0G	0.4-0.63	145.9
3UA5040-1K	8-12.5	124.3	3UA5940-0J	0.63-1	145.9
3UA5040-2S	10-14.5	124.3	3UA5940-0K	0.8-1.25	145.9
3UA5240-0A	0.1-0.16	127.4	3UA5940-1A	1-1.6	145.9
3UA5240-0C	0.16-0.25	127.4	3UA5940-1B	1.25-2	145.9
3UA5240-0E	0.25-0.4	127.4	3UA5940-1C	1.6-2.5	145.9
3UA5240-0G	0.4-0.63	127.4	3UA5940-1D	2-3.2	145.9
3UA5240-0J	0.63-1	127.4	3UA5940-1E	2.5-4	145.9
3UA5240-0K	0.8-1.25	127.4	3UA5940-1F	3.2-5	145.9
3UA5240-1A	1-1.6	127.4	3UA5940-1G	4-6.3	145.9
3UA5240-1B	1.25-2	127.4	3UA5940-1H	5-8A	145.9
3UA5240-1C	1.6-2.5	127.4	3UA5940-1J	6.3-10	145.9
3UA5240-1D	2-3.2	127.4	3UA5940-1K	8-12.5	145.9
3UA5240-1E	2.5-4	127.4	3UA5940-2A	10-16A	162.3
3UA5240-1F	3.2-5	127.4	3UA5940-2B	12.5-20	162.3
3UA5240-1G	4-6.3	127.4	3UA5940-2C	16-25	162.3
3UA5240-1H	5-8	127.4	3UA5940-2D	20-32	162.3
3UA5240-1J	6.3-10	127.4	3UA5940-2E	25-40	179.8
3UA5240-1K	8-12.5	127.4	3UA5940-2M	32-45	179.8
3UA5240-2A	10-16	129.4	3UA5940-2T	40-57	179.8
3UA5240-2B	12.5-20	129.4	3UA5940-2P	50-63	179.8
3UA5240-2C	16-25	129.4	3UA6040-2H	55-80	357
3UA5440-1G	4-6.3	131.4	3UA6040-2W	63-90	357
3UA5440-1J	6.3-10	131.4	3UA6040-2X	80-110	357
3UA5440-2A	10-16	131.4	3UA6040-3H	90-120	397
3UA5440-2B	12.5-20	131.4	3UA6040-3J	110-135	397
3UA5440-2C	16-25	131.4	3UA6140-2H	55-80	371
3UA5440-2D	20-32	131.4	3UA6140-2W	63-90	371
3UA5440-2Q	25-36	131.4	3UA6140-2X	80-110	371
3UA5540-1A	1-1.6	142.8	3UA6140-3H	90-120	413

3UA5540-1B	1.25-2	142.8	3UA6140-3J	110-135	413
3UA5540-1C	1.6-2.5	142.8	3UA6140-3K	120-150	413
3UA5540-1D	2-3.2	142.8	3UA6240-2H	55-80	312
3UA5540-1E	2.5-4	142.8	3UA6240-2W	63-90	312
3UA5540-1F	3.2-5	155.1	3UA6240-2X	80-110	312
3UA5540-1G	4-6.3	155.1	3UA6240-3H	90-120	343
3UA5540-1H	5-8	155.1	3UA6240-3J	110-135	343
3UA5540-1J	6.3-10	155.1	3UA6240-3K	120-150	343
3UA5540-1K	8-12.5	155.1	3UA6240-3L	135-160	373
3UA5540-2A	10-16	155.1	3UA6240-3M	150-180	373
3UA5540-2B	12.5-20	155.1	3UA6640-2K	80-125	1270
3UA5540-2C	16-25	155.1	3UA6640-3B	125-200	1270
3UA5540-2D	20-32	155.1	3UA6640-3C	160-250	1524
3UA5540-2Q	25-36	155.1	3UA6640-3D	200-320	1524
3UA5540-2R	32-40	155.1	3UA6640-3E	250-400	1524

7、热继电器附件

型号	名称	所配接触器型号	单价
3UX1418	连接支座	与3UA50配合组成独立安装产品	46.8
3UX1420		与3UA52、3UA54配合组成独立安装产品	46.8
3UX1421		与3UA58配合组成独立安装产品	46.8
3UX1424		与3UA55配合组成独立安装产品	53.2
3UX1425		与3UA60配合组成独立安装产品	46.8

8、3VU系列空气开关

型号	整定电流范围 (A)	单价	型号	整定电流范围 (A)	单价
3VU1340-1MB00	0.1-0.16	311	3VU1340-1NJ00	3.2-5	311
3VU1340-1MC00	0.16-0.24	311	3VU1340-1NK00	5-8A	311
3VU1340-1MD00	0.24-0.4	311	3VU1340-1NL00	8-13A	320
3VU1340-1ME00	0.4-0.6	311	3VU1640-1LS00	45-63	1235
3VU1340-1MF00	0.6-1	311	3VU1640-1MG00	1-1.6	934
3VU1340-1MG00	1-1.6	311	3VU1640-1MH00	1.6-2.4	934
3VU1340-1MH00	1.6-2.4	311	3VU1640-1MJ00	2.4-4	934
3VU1340-1MJ00	2.4-4	311	3VU1640-1MK00	4-6A	934
3VU1340-1MK00	4-6A	311	3VU1640-1ML00	6-10A	934
3VU1340-1ML00	6-10A	311	3VU1640-1MM00	10-16A	934
3VU1340-1MM00	10-16A	330	3VU1640-1MN00	16-25	1034
3VU1340-1MN00	14-20	351	3VU1640-1MP00	22-32	1068
3VU1340-1MP00	18-25	371	3VU1640-1MQ00	28-40	1168
3VU1340-1NH00	2-3.2	311	3VU1640-1MR00	36-52	1235

9、空气开关附件

型号	名称	所配空开	结构	单价
3VU9131-3AA00	辅助触头	3VU1340	1a1b	97
3VU9131-7AA00	短路故障显示器		1a1b	133
3VU9132-0AB15	欠压脱扣器		AC230V	270
3VU9132-0AB25			AC240V	270
3VU9132-0AB17			AC400V	270

3VU9132-0AB18	分励脱扣器	3VU1640	AC415V	270
3VU9132-0AB50			AC24V	374
3VU9132-0AB59			AC42V	270
3VU9132-0AB55			AC230V	269
3VU9132-0AB65			AC240V	270