









(九) 旋转编码器





外型	型号	每转脉冲数	单价	型号	每转脉冲数	单价
	E30S4-脉冲-X-X-(5, 24) 轴径: 4mm(外径30MM)	100P/R-500P/R	500	E40HB8-脉冲-X-X-(5, 24)	1P/R-300P/R	652
		1000P/R-1024P/R	603		360P/R-1800P/R	704
		3000P/R	821		2000P/R-3600P/R	730
			5000P/R		1026	
	E30S4-脉冲-X-L-5 轴径: 4mm (外径30MM)	100P/R-500P/R	501	E40HB8-脉冲-X-L-5	1P/R-300P/R	730
		1000P/R-1024P/R	603		360P/R-1800P/R	756
		3000P/R	883		2000P/R-3600P/R	782
	E40S6-脉冲-X-X-(5, 24) 轴径: 6mm	1P/R-300P/R	548	E40HBX-脉冲-X-X-(5, 24) HOLE: φ 6. 10. 12mm	5000P/R	1088
		360P/R-1800P/R	652		1P/R-300P/R	704
		2000P/R-3600P/R	718		360P/R-1800P/R	730
	E40S6-XXX-6-L-5	5000P/R	924	E40HBX-脉冲-X-X-(5, 24) HOLE: φ 6. 10. 12mm	2000P/R-3600P/R	756
		1P/R-300P/R	652		5000P/R	1102
360P/R-1024P/R		718	E40HBX-脉冲-X-L-5 HOLE: φ 6. 10. 12mm		1P/R-300P/R	756
1200P/R-3600P/R	782	360P/R-1800P/R		782		
5000P/R	985	2000P/R-3600P/R		809		
E40S8-脉冲-X-X-(5, 24) 轴径: 8mm	1P/R-300P/R	614	E50S8-脉冲-X-X-(5, 24)	5000P/R	1164	
	360P/R-1024P/R	718		1P/R-600P/R	600	
	1200P/R-3600P/R	770		800P/R-3600P/R	730	
E40S8-脉冲-8-L-5	5000P/R	1038	E50S8-脉冲-X-X-(5, 24)	5000P/R	985	
	1P/R-300P/R	718		6000P/R	1108	
	360P/R-1024P/R	782		8000P/R	1273	
E40S8-脉冲-8-L-5	1200P/R-3600P/R	849	E50S8-脉冲-X-L-5	1P/R-600P/R	730	
	5000P/R	1099		800P/R-3600P/R	848	
	1P/R-300P/R	652		5000P/R	1047	
E40H8-脉冲-X-X-(5, 24) 孔径: 8mm	360P/R-1800P/R	704	E50S8-脉冲-X-L-5	6000P/R	1170	
	2000P/R-3600P/R	730		8000P/R	1334	
	5000P/R	1026		E80H30, 32-脉冲-3-X-(5, 24)	60P/R-512P/R	1174
E40HX-脉冲-X-X-(5, 24) 孔径: 6, 10, 12mm	1P/R-300P/R	704	1024P/R		1565	
	360P/R-1800P/R	730	E80H30, 32-脉冲-6-L-5		60P/R-512P/R	1174
	2000P/R-3600P/R	756		1024P/R	1565	
5000P/R	1102	E100H35-脉冲-3-X-(5, 24)		60P/R-1024P/R	1565	
E40H8-脉冲-6-L-5 孔径: 8mm	1P/R-300P/R		730	10000P/R	2094	
	360P/R-1800P/R		756	E100H35-脉冲6-L-5	60P/R-1024P/R	1565
	2000P/R-3600P/R	782	10000P/R		2155	
5000P/R	1088	E68S15-1024-6-L-5	1024P/R		1304	
E40HXX-脉冲-6-L-5 孔径: 6, 10, 12mm	1P/R-300P/R		756	EP50S8-脉冲-X-X-(5, 24)	分辨率: 45, 64, 128, 180, 256, 360, 512, 720, 1024	963
	360P/R-1800P/R		782			
	2000P/R-3600P/R	809				
COUPLING联轴器	5000P/R	1164	COUPLING联轴器	4, 6, 8, 10 mm	130	
	1P/R-300P/R	756				
	360P/R-1800P/R	782				
	ENC-1-X-X-5	1: A, B	691	ENH-脉冲-X-X-5	25, 100P/R	821
		ENC-1-X-X-24	1: A, B			
	ENA-脉冲-X-X-(5, 24)	1P/R-800P/R	600	ENH-脉冲-X-L-5		821
		1000P/R-3600P/R	730	ENH-100-1-1		821
		5000P/R		ENH-100-1-L		821






外型	型号	相位	单价	型号	相位	单价
	ENP-1XX-006, 008, 012, 016, 024, 360-1, 2	0: 负逻辑 1: 正逻辑	1565			

(十) 接近开关

外型	型号	检测距离	规格	电源	单价			
	PRT08-1.5D0, 1.5DC	1.5mm	电感圆柱型 直流2线 DO:常开输出 DC:输出常闭	24V DC (20-30VDC)	140			
	PRT08-2D0, 2DC	2mm			140			
	PRT12-2D0, 2DC	2mm			121			
	PRT12-4D0, 4DC	4mm			121			
	PRT18-5D0, 5DC	5mm			121			
	PRT18-8D0, 8DC	8mm			121			
	PRT30-10D0, 10DC	10mm			130			
	PRT30-15D0, 15DC	15mm			130			
	PR08-1.5DN, 1.5DP	1.5mm	电感圆柱型;直流3线 DN:NPN输出 DP:PNP输出	12-24VDC (10-30VDC)	140			
	PR08-1.5DN, 1.6DP				140			
	PR08-2DN, 2DP2				140			
	PRS12-2DN, 2DP	2mm	直流短型3线 DN:NPN常开输出 DP:PNP常开输出	12-24VDC (10-30VDC)	130			
	PRS12-2DN2				130			
	PRS12-4DN, 4DP	4mm			130			
	PRS12-4DN2				130			
		PR12-2DN, 2DP	2mm	电感圆柱型 直流3线 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	12-24VDC (10-30VDC)	121		
PR12-2DN2, 2DP2		121						
PR12-4DN, 4DP		4mm	121					
PR12-4DN2, 4DP2			121					
PR18-5DN, 5DP		5mm	121					
PR18-5DN2, 5DP2			12-24VDC (10-30VDC)			121		
PR18-8DN, 8DP			121					
PR18-8DN2, 8DP2		8mm	121					
		PR30-10DN, 10DP	10mm			电感圆柱型直流3线;DN: NPN常开输出;DP:PNP常开输 出;DN2:NPN常闭输 出;DP2:PNP常闭输出	12-24VDC (10-30VDC)	141
		PR30-10DN2, 10DP2						141
	PR30-15DN, 15DP	15mm	141					
	PR30-15DN2, 15DP2		141					
	PR12-2A0. 2AC	2mm	电感圆柱型 交流2线 A0:常开输出 AC:输出常闭	110V-220VAC (90- 250VAC)	143			
	PR12-4A0. 4AC	4mm			143			
	PR18-5A0. 5AC	5mm			143			
	PR18-8A0. 8AC	8mm			143			
	PR30-10A0. 10AC	10mm			156			
	PR30-15A0. 15AC	15mm			156			
	PRL08-1.5DN, 1.5DP	1.5mm	直流2线长型 DN:NPN常开输出 DP:PNP常开输出	12-24VDC (10-30VDC)	181			
	PRL08-1.5DN2, 1.5DP2							
	PRL08-2DN, 2DP	2mm		130				
	PRL08-2DN2, 2DP2							
	PRL12-2DN, 2DP	2mm		130				
	PRL12-4DN, 4DN2, 4DP	4mm		130				
	PRL18-5DN, 5DP	5mm		130				
	PRL18-5DN2, 5DP2			130				

外型	型号	检测距离	规格	电源	单价	
	PRL18-8DN, 8DP	8mm	直流2线长型 DN:NPN常开输出 DP:PNP常开输出	12-24VDC (10-30VDC)	130	
	PRL18-8DN2, 8DP2				130	
	PRL30-10DN, 10DP	10mm			156	
	PRL30-10DN2, 10DP2				156	
	PRL30-15DN, 15DP	15mm		12-24VDC	156	
	PRL30-15DN2, 15DP2				156	
	PRL18-5AO, 5AC	5mm	交流2线长型 AO:常开输出 AC:输出常闭	AC100-240V	143	
	PRL18-8AO, 8AC	8mm			143	
	PRL30-10AO, 10AC	10mm			170	
	PRL30-15AO, 15AC	15mm			170	
	PRCMT12-2DO, 2DC	2mm	电感圆柱型 直流2线 接插型 DO:常开输出 DC:输出常闭	DC24V	130	
	PRCMT12-4DO, 4DC	4mm			130	
	PRCMT18-5DO, 5DC	5mm			130	
	PRCMT18-8DO, 8DC	8mm			130	
	PRCMT30-10DO, 10DC	10mm			143	
	PRCMT30-15DO, 15DC	15mm			143	
	PRCM12-2DN, 2DP	2mm	电感圆柱型 直流标准 接插型 DO:常开输出 DC:输出常闭	12-24VDC	130	
	PRCM12-2DN2, 2DP2				130	
	PRCM12-4DN, 4DP	4mm			130	
	PRCM12-4DN2, 4DP2				130	
PRCM18-5DN, 5DP	5mm	12-24VDC		130		
PRCM18-5DN2, 5DP2				130		
PRCM18-8DN, 8DP	8mm	130				
PRCM18-8DN2, 8DP2		130				
	PRCM30-10DN, 10DP	10mm	12-24VDC	156		
	PRCM30-10DN2, 10DP2			156		
	PRCM30-15DN, 15DP	15mm		156		
	PRCM30-15DN2, 15DP2			156		
嵌入式	PRCM12-2AO, 2AC	2mm	电感圆柱型 交流标准 接插型 AO:常开输出 AC:输出常闭	110V-220VAC (90-250VAC)	164	
	PRCM12-4AO, 4AC	4mm				
	PRCM18-5AO, 5AC	5mm				
	PRCM18-8AO, 8AC	8mm			192	
	PRCM30-10AO, 10AC	10mm				
	PRCM30-15AO, 15AC	15mm				
	PRCML18-5DN, 5DP	5mm	电感圆柱型 直流加长 接插型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	12-24VDC (10-30VDC)	143	
	PRCML18-5DN2, 5DP2				143	
	PRCML18-8DN, 8DP	8mm			143	
	PRCML18-8DN2, 8DP2				143	
	PRCML30-10DN, 10DP	10mm		12-24VDC (10-30VDC)	183	
	PRCML30-10DN2, 10DP2				183	
	PRCML30-15DN, 15DP	15mm		183		
	PRCML30-15DN2, 15DP2			183		
	外露型	PRCML18-5AO, 5AC		5mm	110V-220VAC (90-250VAC)	164
		PRCML18-8AO, 8AC		8mm		192
		PRCML30-10AO, 10AC		10mm		
		PRCML30-15AO, 15AC		15mm		

外型	型号	检测距离	规格	电源	单价			
	PRD18-7DN, 7DP	7mm	电感圆柱型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	12-24VDC	162			
	PRD18-7DN2, 7DP2	7mm			186			
	PRD18-14DN, 14DP	14mm			162			
	PRD18-14DN2, 14DP2	14mm			186			
	PRD12-4DN	4mm			162			
	PRD12-4DN2	4mm			186			
	PRD12-4DP	4mm			162			
	PRD12-4DP2	4mm			186			
	PRD12-8DN	8mm			162			
	PRD12-8DN2	8mm			186			
	PRD12-8DP	8mm			162			
	PRD12-8DP2	8mm			186			
	PRWT12-2D0, 2DC	2mm			电感圆柱型 直流2线电缆接插型 D0:常开输出 DC:输出常闭	12-24VDC	137	
	PRWT12-4D0, 4DC	4mm						
PRWT18-5D0, 5DC	5mm							
PRWT18-8D0, 8DC	8mm							
PRWT30-10D0, 10DC	10mm	100HZ, 外露型	DC24V	164				
PRWT30-15D0, 15DC	15mm							
PRW08-1.5DN	1.5mm		DC12-24V	172				
	PRW12-2DN, 2DP	2mm	电感圆柱型 电缆输出接插型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	12-24VDC (10-30VDC)	137			
	PRW12-2DN2, 2DP2							
	PRW12-4DN, 4DP	4mm						
	PRW12-4DN2, 4DP2							
	PRW18-5DN, 5DP	5mm						
	PRW18-5DN2, 5DP2							
	PRW18-8DN, 8DP	8mm						
	PRW18-8DN2, 8DP2							
	PRW30-10DN, 10DP	10mm						
	PRW30-10DN2, 10DP2							
PRW30-15DN, 15DP	15mm							
PRW30-15DN2, 15DP2								
 嵌入型	PRW12-2A0, 2AC	2mm		110V-220VAC (90-250VAC)	164			
	PRW12-4A0, 4AC	4mm						
	PRW18-5A0, 5AC	5mm						
	PRW18-8A0, 8AC	8mm						
	PRW30-10A0, 10AC	10mm						
	PRW30-15A0, 15AC	15mm						
	PRWL18-5DN, 5DP	5mm				电感圆柱型 加长电缆输出接插型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DP2:PNP常闭输出	12-24VDC (10-30VDC)	144
	PRWL18-5DN2, 5DP2							
	PRWL18-8DN, 8DP	8mm						
	PRWL18-8DN2, 8DP2							
PRWL30-10DN, 10DP	10mm							
PRWL30-10DN2, 10DP2								
PRWL30-15DN, 15DP	15mm							
PRWL30-15DN2, 15DP2								
PRWL18-5A0, 5AC	5mm		110V-220VAC (90-	164				
 上面检测 (U型)	PRW12-2A0, 2AC	2mm		110V-220VAC (90-	171			
	PRW12-4A0, 4AC	4mm						
	PRW18-5A0, 5AC	5mm						
	PRW18-8A0, 8AC	8mm						
	PRW30-10A0, 10AC	10mm						
	PRW30-15A0, 15AC	15mm						

外型	型号	检测距离	规格	电源	单价	
	PRWL18-8A0, 8AC	8mm		250VAC)	104	
	PRWL30-10A0, 10AC	10mm		110V-220VAC (90-250VAC)	192	
	PRWL30-15A0, 15AC	15mm				
	PRAT12-2D0, 2DC	2mm	直流2线防溅型 DO:常开输出 DC:输出常闭	24VDC (20-30V DC)	222	
	PRAT18-5D0, 5DC	5mm			244	
	PRAT30-10D0, 10DC	10mm			301	
	PRA12-2DN. 2DP	2mm	电感圆柱型 防溅型 DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出	12-24VDC (10-30VDC)	222	
	PRA12-2DN2. 2DP2				222	
	PRA18-5DN. 5DP	5mm			244	
	PRA18-5DN2. 5DP2				244	
	PRA30-10DN. 10DP	10mm			301	
	PRA30-10DN2. 10DP2				301	
	PRA12-2A0, 2AC	2mm			110V-220VAC (90-250VAC)	241
	PRA18-5A0, 5AC	5mm				261
	PRA30-10A0, 10AC	10mm				313
	CR18-8DN, 8DP	8mm			DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出	12-24VDC (10-30VDC) 电容圆柱型
	CR18-8DN2		183			
	CR30-15DN, 15DP	15mm	222			
	CR30-15DN2		222			
	PSNT17-5D0, 5DC	5mm	700HZ, 常开/常闭	DC24V	70	
	PSNT17-5D0U, 5DCU		700HZ, 常开/常闭, 上面探测型			
	PS12-4DN. 4DP, 4DN2	4mm	DN:NPN常开输出 DP:PNP常开输出 DN2:NPN常闭输出 DNU:NPN常开输出, 上面检测型 DPU:PNP常开输出, 上面检测型 DN2U:NPN常闭输出, 上面检测型	12-24VDC (10-30VDC) 电感方型	117	
	PS12-4DNU, 4DPU, 4DN2U					
	PSN17-5DN, 5DP, 5DN2	5mm			70	
	PSN17-5DNU, 5DPU					
	PSN17-5DN2U					
	PSE17-5DN, 5DP	5mm			40	
	PSN17-8DN, 8DP	8mm			70	
	PSN17-8DN2, 8DP2					
	PSN17-8DNU, 8DPU					
	PSN17-8DN2U					
	PSN17-5DN-F	5mm				
	PSN17-8DN, 8DP, 8DN2-F	8mm				
	PSN17-8DNU, 8DPU-F					
	PSN17-8DN2U-F					
	PS50-30DN, 30DP	30mm				
	PS50-30DN2, 30DP2		235			
	AS80-50DN3, 50DP3	50mm	DC12-48V	554		
	PFI25-8DN, 8DP	8mm	200HZ	DC12-24VDC 直流扁平型	130	
	PFI25-8DN2, 8DP2					
	PSN25-5DN, 5DP	5mm	直流新式方型 常开输出 出 出 出	DN:NPN DP:PNP常开输 DN2:NPN常闭输 DP2:PNP	98	
	PSN25-5DN2, 5DP2				98	
	PSN30-10DN, 10DP	10mm			117	
	PSN30-10DN2, 10DP2	10mm				
	PSN30-15DN, 15DP	15mm				

	PSN30-15DN2, 15DP2	15mm	常闭输出		
	PSN40-20DN, 20DP	20mm			156
	型 号	检测距离	规 格	电 源	单价
	PSN40-20DN2, 20DP2	20mm			156
	PSN25-5A0, 5AC	5mm	交流新式方型 A0: 常开输出 AC: 输出常闭	AC100-240V	130
	PSN30-10A0, 10AC	10mm			143
	PSN30-15A0, 15AC	15mm			
	PSN40-20A0, 20AC	20mm			222
	PET18-5	5mm			117
	PT4-2D, 3DN, 3DP	4路中继连接盒	2D:DC2线使用	DC12-24V	444
	PT6-2D, 3DN, 3DP	6路中继连接盒	3DN:DC3线NPN使用		509
	PT8-2D, 3DN, 3DP	8路中继连接盒	3DP:DC3线PNP使用		574
	P96-M12-1	防水盖	可保护平时很少用的连接器孔渗水或渗油		21
	P90-M12, M18, M30	接近传感器固定架	齐平型圆柱接近开关适用		4
	P90-R12, R18, R30		圆柱型接近开关适用		4
连接器防护罩	PT1-D, A	面板安装连接头(适用于DC/AC外露型接近开关)			39
	PT2-D, A	面板安装连接头(适用于DC/AC平头型接近开关)			39

(十一) 连接线缆

型 号	类 型	单 价	型 号	类 型	单 价
CID2-2, 3-2, 2-2-I	插座型	46	C1D4-5, C2D4-5	DC型 (插头-插座)	83
CLD2-2, 3-2, 2-2-I		46	C1D4-5P		
CIA2-2, CLA2-2		46	C2D4-2, C3D4-2	DC型(插头-插座)	65
CID2-5, 3-5, 2-5-I		65	C3D4-5, C4D4-5		
CLD2-5, 3-5, 2-5-I		65	C1A4-5, C2A4-5	AC型 (插座-插头)	83
CIA2-5, CLA2-5		65	C1A4-5P		
C1D4-2, C2D4-2	DC型 (插头-插座)	65	C3A4-5, C4A4-5	插头型	46
C1D4-2P			CID2-2P, CLD2-2P		
C3D4-2, C4D4-2			CID2-5P, CLD2-5P		
C1A4-2, C2A4-2	AC型 (插座-插头)	65	CID3-2P, CLD3-2P		
C1A4-2P			CID3-5P, CLD3-5P		
C3A4-2, C4A4-2			CIA2-2P, CLA2-2P		
			CIA2-5P, CLA2-5P		65

(十二) 传感器控制器


外型	型 号	输 出	功 能	说 明	电 源	单 价
	PA-12	定时1c	通用型	NPN/PNP内部转换输入	AC110/220V	143
	PA-12-PG				AC110/220V	226
	PA-12-PGP			PNP		
	PA10-U	定时1c	高性能	NPN输入	AC100-240V	372
	PA10-V, VP	NPN 0. C. ×2	通用	NPN/PNP输入		323
	PA10-W, WP	定时2c	2通道	NPN/PNP输入		

串行通信转换模块

外型	型 号	通 讯 类 型	说 明	电 源	单 价
	SCM-38I	半双工型	RS232(2线通讯型)	12-24VDC	150

(十三) 开关电源

外 型	型 号	电 源	单 价	型 号	电 源	单 价
-----	-----	-----	-----	-----	-----	-----

	SP-0305	AC100-240V	183	SPA-050-12	AC100-240V	477
	SP-0312			SPA-030-24		398
	SP-0324		SPA-050-24	477		
	SPA-030-05		183	SPA-075-24	AC100-120/AC200-	750
	SPA-050-05		183	SPA-100-24	240V	742
	SPA-030-12		398			

## (十四) 压力传感器

外型	型号	检测距离	压力种类	电源	压力范围	单价
	PSA-V01 (P)	正方形	负压	DC12-24V	0.0~-101.3kPa	652
	PSA-01 (P)		标准		0.0~100.0kPa	
	PSA-1 (P)		标准		0.01~1000kPa	
	PSA-C01 (P)		复合		-100~100kPa	
	PSB-V01 (P)	长方形	负压	DC12-24V	0.0~-101.3kPa	652
	PSB-01 (P)		标准		0.0~100.0kPa	
	PSB-1 (P)		标准		0.01~1000kPa	
	PSB-C01 (P)		复合		-100~100kPa	
配件	PS0-01	PSA外壳 (黑色)				44
	PS0-02	PS0-01 保护盖				30

## (十五) 步进电机/驱动器/控制器

步进电机驱动器	型号	外型尺寸	驱动电流	驱动方式	电源	单价
	KR5MC	77×45×32	1.4A	0.72/0.36	20-40VDC 3A	1189
	KR-55MC	105×74×38		Micro		2000
	MD5-MF14	170×130×39		STEP (0.009)	100-240VAC	2660
	KR-505G	215×150×62	2.8A	0.72/0.36	100-115VAC	3130
标准单轴型 (5线型)	型号	激磁最大静止转矩 (kgfcm)	单价	型号	激磁最大静止转矩 (kgfcm)	单价
	A1K-S543	1.3	617	A16K-G569	16.6	1164
	A2K-S544	1.8	657	A21K-M596	21	1612
	A3K-S545	2.4		A21K-G596		
	A4K-S564	4.2	710	A41K-M599	41	2283
	A4K-M564		575	A41K-G599		
	A8K-S566	8.3	743	A63K-M5913	63	2841
	A8K-M566		603	A63K-G5913		2991
	A16K-M569	16.6	794			
标准单轴型 (标准接线:10线型)	型号	激磁最大静止转矩 (kgfcm)	单价	型号	激磁最大静止转矩 (kgfcm)	单价
	A1K-S543-S	1.3	712	A16K-G569-S	16.6	1094
	A2K-S544-S	1.8	754	A21K-M596-S	21	1712
	A3K-S545-S	2.4		A21K-G596-S		
	A4K-S564-S	4.2	821	A41K-M599-S	41	2390
	A4K-M564-S		672	A41K-G599-S		
	A8K-S566-S	8.3	856	A63K-M5913-S	63	2949
	A8K-M566-S		699	A63K-G5913-S		
	A16K-M569-S	16.6	891			
标准双轴型 (5线型)	型号	激磁最大静止转矩 (kgfcm)	单价	型号	激磁最大静止转矩 (kgfcm)	单价
	A1K-S543W	1.3	645	A16K-G569W	16.6	1178
	A2K-S544W	1.8	685	A21K-M596W	21	1639
	A3K-S545W	2.4		A21K-G596W		

A4K-S564W	4.2	727	A41K-M599W	41	2347
A4K-M564W		590	A41K-G599W		
A8K-S566W	8.3	759	A63K-M5913W	63	2878
A8K-M566W		617	A63K-G5913W		
A16K-M569W	16.6	809			

标准双轴型 (标准结 线: 10线 型)	型号	激磁最大静止转矩 (kgfcm)	单价	型号	激磁最大静止转矩 (kgfcm)	单价
	A1K-S543W-S	1.3	727	A16K-G569W-S	16.6	1110
	A2K-S544W-S	1.8	767	A21K-M596W-S	21	1755
	A3K-S545W-S	2.4		A21K-G596W-S		
	A4K-S654W-S	4.2	839	A41K-M599W-S	41	2445
	A4K-M654W-S		685	A41K-G599W-S		
	A8K-S566W-S	8.3	873	A63K-M5913W-S	63	3003
	A8K-M566W-S		712	A63K-G5913W-S		
	A16K-M569W-S	16.6	904			
标准单孔型	AH1K-S543	1.3	1162	AH16K-G569	16.6	1438
	AH2K-S544	1.8	1120	AH21K-M596	21	1950
	AH3K-S545	2.4	1088	AH21K-G596		1952
	AH4K-S564	4.2	1202	AH41K-M599	41	3219
	AH4K-M564					
	AH8K-S566	8.3	1235	AH63K-M5913	63	2604
	AH8K-M566			AH63K-G5913		2608
	AH16K-M569	16.6	1438			
标准双孔型	AH4K-S564W	4.2	1217	AH21K-M596W	21	1968
	AH4K-M564W			AH21K-G596W		1970
	AH8K-S566W	8.3	1250	AH41K-M599W	41	3240
	AH8K-M566W					
	AH16K-M569W	16.6	1454	AH63K-M5913W	63	2622
	AH16K-G569W			AH63K-G5913W		2624
减速机 (单轴, 5 线结线)	A35K-M566-G5	35	2252	A200K-M599-G7.2	200	3198
	A40K-M566-G7.2	40		A200K-G599-G7.2		3228
	A50K-M566-G10	50		A200K-M599-G10	200	3226
	A140K-M599-G5	140	3038	A200K-G599-G10		3200
	A140K-G599-G5	140	3114			
减速机 (双轴, 5 线结线)	A35K-M566W-G5	35	2291	A200K-M599W-G7.2	200	3202
	A40K-M566W-G7.2	40		A200K-G599W-G7.2		3202
	A50K-M566W-G10	50		A200K-M599W-G10	200	3204
	A140K-M599W-G5	140		A200K-G599W-G10		3212
	A140K-G599W-G5	140		3128		
减速机+ 带电磁制动 型	A35K-M566-GB5	35	2786	A200K-M599-GB7.2	200	4420
	A40K-M566-GB7.2	40	2810	A200K-G599-GB7.2		4458
	A50K-M566-GB10	50	2824	A200K-M599-GB10	200	4420
	A140K-M599-GB5	140	4268	A200K-G599-GB10		4458
	A140K-G599-GB5	140	4342			
带电磁震动	A4K-S564-B	4.2	1537	A8K-M566-B	8.3	1577
	A4K-M564-B			A16K-M569-B	16.6	1854



	A8K-S566-B	8.3	1577	A16K-G569-B	10.0	1094
步进马达	A35K-M566-R5	35	2030	A50K-M566W-R10	50	2074
	A35K-M566W-R5		2050	A35K-M566-RB5	35	2906
	A40K-M566-R7.2	40	1992	A40K-M566-RB7.2	40	2908
	A40K-M566W-R7.2		1984	A50K-M566-RB10	50	3012
	A50K-M566-R10	50	2054			